

EMH Wire Rope Hoists

Dimensions and Specifications

Hoist Model: EM 5000E

Trolley Type: Monorail for Single Girder Cranes

Reeving: 8 to 2

Capacities: 10 and 15 tons


Rope Diameter (mm):	2 x 11
Drum Diameter:	11.625"
Sheave Diameter:	13"
Hoist Motor HP:	20.4/3.4
Trolley Motor HP:	2x0.6/0.15
Trolley Wheel Diameter:	8
Speeds (fpm):	16/2.6
Trolley Speed (fpm):	63/16

Dimensions (inches):		
Refer to drawing below. C, M and R dimensions shown in adjacent tables.	A:	24.875
	B:	25.5
	G:	15.625
	H:	12
	I:	6.125
	K:	6.125
	N-Min:	7.875
	N-Max:	20
Maximum Flange Thickness:		1.929

Duty Service Classification		FEM	HMI
Capacity in US Tons	10	3	H4
	15	2	H4

Available Lifts (ft): L, M, R and Wt. vary with lift.				
	L (in.)	M (in.)	R (in.)	Wt. (lbs.)
6	27.5	27.5	42.75	3600
15	33.5	33.5	54.75	3690
27	41	41	69.75	3800
33	44.125	44.125	76	3910

C Dimension - inches:			
Varies with flange width (N)	N<12"	12"<N<16"	N>16"
	30.375	30.375	35



E·M·H
Engineered Material Handling