



## Trolley (MTS/MTD)

Features:

- Heavy duty construction
- Low profile design
- Adjustable to any standard I-beam
- Direct connection for shorter headroom

Model	Working Load Limit (tonne)	Travel Motor Output (Kw)	Travel Speed (m/min)	A	B	C	D	E	F (Trolley Wheel Centres)	G	Minimum Radius of Curve (m)	Net Weight (kg)
MTS 100	1	0.25	20	328	173	294	98	75-125	149	246	1.3	40
MTD 100	1	0.25 / 0.08	20/7	328	173	294	98	75-125	149	246	1.3	40
MTS 200	2	0.25	20	328	173	322	111	100-150	161	272	1.5	45
MTD 200	2	0.25 / 0.08	20/7	328	173	322	111	100-150	161	272	1.5	45
MTS 300	3	0.6	20	368	180	356	117	125-175	172	297	1.8	65
MTD 300	3	0.6 / 0.2	20/7	368	180	356	117	125-175	172	297	1.8	65
MTS 500	5	0.6	20	372	184	386	127	125-175	183	320	2	89
MTD 500	5	0.6 / 0.2	20/7	372	184	386	127	125-175	183	320	2	89
MTS 750	7.5	0.9	13	380	193	454	167	150-200	229	400	3	155
MTS 1000	10	1.5	15	471	193	560	205	150-200	278	450	3.5	218

