




Tusker® Duplex Flat Slings (DFS strops)

SLINGS & TIE DOWN EQUIPMENT

Type	Capacity/ Colour	Working Load Limits for 1 Lifting Slings		Working Load Limits for 2 Lifting Slings									
		Straight	Chocked	0°-7°		7°-45°		45°-60°					
				1	0.8	2	1.4	1.4	1.12	1	0.8		
DFS 30/	WLL.1t Purple	1000	.800	2000	1400	1400	.1400	1000	1000	1000	1000	1000	800
DFS 60	WLL.2t Green	2000	1600	4000	2800	2800	2800	2000	2000	2240	2000	2500	1600
DFS 75	WLL.2.5t Olive Green	2500	2000	5000	3500	3500	3500	2500	2800	2800	2500	3000	2000
DFS 90	WLL.3t Yellow	3000	2400	6300	4200	4200	4200	3000	3360	3360	3000	3400	2400
DFS 120	WLL.4t Grey	4000	3200	8000	5600	5600	5600	4000	4480	4480	4000	4600	3200
DFS 150	WLL.5t Red	5000	4000	10000	7000	7000	7000	5000	5600	5600	5000	5800	4000
DFS 180	WLL.6t Brown	6000	4800	12000	8400	8400	8400	6000	6720	6720	6000	7000	4800
DFS 240	WLL.8t Blue	8000	6400	16000	11200	11200	11200	8000	8960	8960	8000	9600	6400
DFS 300	WLL.10t Orange	10000	8000	20000	14000	14000	14000	10000	11200	11200	10000	12000	8000



Features:

- Duplex (for double safety) lifting sling made from high tenacity polyester fibres
- Manufactured in accordance with EN 1492-1/ SANS 94-1 2003 (F.O.S. 7:1)
- Temperature range of -40°C to +100°C
- Available in any length up to 50t WLL
- Double stitching with reinforced eyes

Protection Sleeves

- Extreme conditions: "Stobitex" - steel plates/coils, polyurethane bonded or sleeve
- Hard conditions: "Polytex" - concrete/granite, polyester sleeve
- Moderate conditions: "PVC" - wood, PVC layflat sleeve

