



		Leg Max. Working Load Limit Kg						2 Legs Max. Working Load Limit Kg					
		7° <β <45°	45° <β <60°	7° <β <45°	45° <β <60°	7° <β <45°	45° <β <60°	7° <β <45°	45° <β <60°	7° <β <45°	45° <β <60°		
Webbing Sling		1.0	0.8	1.4	1.0	0.7	0.5	1.4	1.0	1.12	0.8		
		1000	800	1400	1000	700	500	1400	1000	1120	800		
Round Sling		2000	1600	2800	2000	1400	1000	2800	2000	2240	1600		
		3000	2400	4200	3000	2100	1500	4200	3000	3360	2400		
Rigging Sling		4000	3200	5600	4000	2800	2000	5600	4000	4480	3200		
		5000	4000	7000	5000	3500	2500	7000	5000	5600	4000		
		6000	4800	8400	6000	4200	3000	8400	6000	6720	4800		
		8000	6400	11200	8000	5600	4000	11200	8000	8960	6400		
		10000	8000	14000	10000	7000	5000	14000	10000	11200	8000		
		12000	9600	16800	12000	8400	6000	16800	12000	13440	9600		
		15000	12000	21000	15000	10500	7500	21000	15000	16800	12000		
		20000	16000	28000	20000	14000	10000	28000	20000	22400	16000		
		25000	20000	35000	25000	17500	12500	35000	25000	28000	20000		
		30000	24000	42000	30000	21000	15000	42000	30000	33600	24000		
		40000	32000	56000	40000	28000	20000	56000	40000	44800	32000		
		50000	40000	70000	50000	35000	25000	70000	50000	56000	40000		
		60000	48000	84000	60000	42000	30000	84000	60000	67200	48000		
		80000	64000	112000	80000	56000	40000	112000	80000	89600	64000		
		100000	80000	140000	100000	70000	50000	140000	100000	112000	80000		
		200000	160000	280000	200000	140000	100000	280000	200000	224000	160000		



- Features:**
- Manufactured in accordance with EN 1492-2/ SANS 94-2 2003 (F.O.S. 7:1)
  - Temperature range of -40°C to +100°C
  - Available in any length and any capacity (WLL)